



Technical Data Sheet-DPH

DPH-4-PH5 Adjustable from 3" to 4 1/4" (77 to 108 mm)

COMPONENTS

The DPH-4-PH5 is composed of 3 pieces: Slope corrector + DPH Top + DPH base

CHARACTERISTICS

Top: ø 6 1/8" Base: ø 7 7/8" Weight: 1 lb. Height adjustable from 3" to 4 1/4" Slope corrector is integrated in the head of the pedestal, providing slope correction from 0-5% (in 0,5 % intervals)


MATERIAL


Copolymer polypropylene (CPP) made from 95% recycled plastics Designed and manufactured in Europe Use of recycled materials exclusively of EU origin Resistant to weathering, sea salts, algae and a wide range of chemicals

Temperature range: -22°F to +176°F

PACKAGING

Pieces per carton: 24 pcs Carton weight: 26.6 lb. Carton dimension: 24" x 16" x 12" Cartons per pallet: 30 pcs Pieces per pallet: 720 pcs Pallet dimensions: 39" x 47" x 87"





APPLICATIONS

Buzon pedestals can be used for a wide range of outdoor applications, such as terraces, pool decks and water features, in landscape areas and on rooftops... Finishing materials can be freely specified by the designer. Accessories are available for applications with various outdoor finishes, such as granite stone pavers, composite / timber decking, ceramic tiles and fibreglass or metal grating panels. Buzon pedestals can be installed on a wide range of solid and stable substrates, such as concrete slabs, cement screeds, waterproof membranes, insulation panels.

Spacer Tabs





Thickness:

1/16", 3/16", 1/4", 5/16", 3/8"

Thickness: 1/8" and 3/16"

Shims







COMPRESSION TEST*

Performed on the full (1/1), half (1/2) and quarter (1/4) surface of the head (1kN=100 kg=224,8 lbF)

Position	Height (mm)	Breaking load (kN)	Breaking load (lbF)
1/1	108	17,03 (1703kg)	3 832
1/2 **	108	11,82 (1182 kg)	2 659
1/4 **	108	6,35 (635 kg)	1 429

* Tests carried out by SIRRIS at 23° C.

** Maximum load per pedestal: take 1/1 value as reference

** Safety recommendation for use of Buzon Pedestals System :

1. Areas reserved for pedestrian access: divide the load indicated in the table by 2 with an additional safety factor of -15%.

2. Areas reserved for industrial and technical applications: divide the load indicated in the table by 4 with an additional safety factor of -15%.

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.



Buzon has a policy of continuous improvement and reserves the right to modify, revise or change the above specifications without notice. This brochure is for descriptive purpose only and is based on the product as on the date of publication of this information.

BPI 2024 © Copyright Buzon Pedestal International SA Buzon DPH® is a registered trade mark of Buzon Pedestal International SA.