



Technical Data Sheet

U-E20-Wall Shim thickness 1/16"
(2 mm)

COMPONENTS

The U-E20-Wall is composed of 1 piece.

CHARACTERISTICS

Weight: **1.5 oz.**

Length: **6 7/8"**

Thickness: **1/16"**

MATERIAL

Material: **SBR**

Hardness Shore A Din 53505: **60-80 SHA**

Color: **Black**

Temperature range: **-22°F to +158°F**

Tensile Strength Din 53504: **3 Mpa**

Elongation at break DIN 53504: **250%**

Resistant to weathering, sea salts, algae and a wide range of chemicals

PACKAGING

Pieces per carton: **240 pcs**

Carton weight: **23.2 lb.**

Carton dimension: **15" x 8" x 5"**

Cartons per pallet: **108 pcs**

Pieces per pallet: **25 920 pcs**

Pallet dimensions: **31" x 47" x 47"**

APPLICATIONS

The **U-E20 Wall** is a 1/16" (2 mm) shim. Placed on the U-Wall support, it stabilises the paver, provides additional acoustic comfort, and compensates for variations in paver thickness.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

